


Product Specifications

FlashLink. HVAC PDF Data Logger

Measurement Range	-40°F to 122°F
Temperature Resolution	0.2°F
Accuracy	±1.0°F from -4°F to 113°F; ±2.0°F above 113°F; ±2.0°F below -4°F
Data Capacity	16,112 points
Data Download Time	30 seconds typical
Battery	Coin Cell Lithium battery
Dimensions	1.93" x 3.62" x 0.67" (49mm x 92mm x 17mm)
Casing	ABS plastic
Weight	1.6 oz. (45.36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, Calibration traceable to NIST, RoHS Compliant
Display	LCD, battery life indicator
Storage Conditions	-4°F to 122°F 0% to 95% RH w/o condensation
PDF Standards	Complies with ISO19005-1, PDF/A, 21 CFR Part 11
Min. System Requirements	Windows PC with current operating system Adobe Reader
Download	Direct USB connection to PC, printer or tablet



Fold-out USB connector

Model 40240	7-Day
°F	99 uses

- One unit can be used multiple times
- No software or PC needed to program logger
- No software needed to download data
- Built-in USB connector, no special reading devices required
- Option to print PDF report directly to printer without using a computer
- Stops recording after downloading data
- Automatically creates secure PDF report and CSV file
- Push-button resets and restarts unit for next use
- Temperature statistics available on LCD
- Service available to custom configure logging parameters, alarms, delayed start

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0194_16C1

