

ESPECIFICACIONES DE PRODUCTO



Feature	Specification
Recording Period	15 Days
Logging Interval	6 min
Measurement Range	-40°F to 122°F (-40°C to 50°C)
Temperature Resolution	0.1°F/°C
Temperature Accuracy	±1.0°F from 14°F to 77°F (±0.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Data Capacity	3823 points
Data Download Time	5 seconds typical for 3823 points
Alarms/Settings	High 36° F (2°C), Low 28° F (-2°C)
Battery	Coin Cell Lithium Battery
Logger Dimensions	1.962" x 3.423" x .575" (50mm x 87mm x 15mm)
Casing	ABS plastic
Logger Weight	1.6 oz. (45.36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, ROHS Compliant
Display	°F Scale on LCD, Red LED Alarm
IP Rating	IP56
Storage Conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
Min. System Requirements	Windows PC with current operating system, FlashPDF software, Adobe Reader
Download Requirements	8-Pin to USB Adapter
DeltaTrak manufactures products under an ISO 90001:2008 registered quality management system Patent No. 6,088, 514	